

Ruby Compact

[Bike Geometry...](#)

Technical Specifications

| | |
|------------------|---|
| FRAME | Specialized FACT 9r carbon, FACT construction, Women's Endurance Geometry and layup, Zertz, threaded BB |
| SWAT | |
| REAR SHOCK | |
| FORK | Specialized Ruby, FACT carbon full monocoque, Zertz |
| HEADSET | 1-1/8" Cr-Mo cartridge bearings, 20mm cone spacer, w/ 20mm of spacers |
| STEM | Specialized Comp-Set, 3D forged alloy, 4-position adjustable, 4-bolt, 31.8mm clamp |
| HANDLEBARS | Specialized Women's Comp, alloy, 123mm drop, 75mm reach |
| TAPE | Specialized Roubaix, w/ 2.5 gel pads |
| FRONT BRAKE | AXIS 1.0 |
| REAR BRAKE | AXIS 1.0 |
| BRAKE LEVERS | Shimano Sora |
| FRONT DERAILLEUR | Shimano Sora, braze-on, 9-speed |
| REAR DERAILLEUR | Shimano Sora, 9-Speed |
| SHIFT LEVERS | Shimano Sora STI, 9-speed |
| CASSETTE | Shimano HG-50, 9-speed, 11-32 |
| CHAIN | KMC X9, w/ reusable Missing Link |
| CRANKSET | Shimano Sora |
| CHAINRINGS | 50/34 |
| BOTTOM BRACKET | Power Spline BB, Cr-Mo axle |
| PEDALS | Nylon flat test ride, loose ball, w/ reflectors |
| FRONT WHEEL | AXIS 1.0 |
| REAR WHEEL | AXIS 1.0 |
| RIMS | |
| FRONT HUB | |
| REAR HUB | |
| SPOKES | |
| FRONT TIRE | Specialized Espoir, 60TPI, foldable aramid bead, double BlackBelt protection, 700x25c |
| REAR TIRE | Specialized Espoir, 60TPI, foldable aramid bead, double BlackBelt protection, 700x25c |
| INNER TUBES | Standard presta valve |
| SADDLE | Body Geometry Women's Riva Sport, 155mm |
| SEATPOST | Specialized Comp, carbon, 27.2mm |
| SEAT BINDER | Integrated, forged alloy |
| EQUIPPED | |
| NOTES | |

Specifications subject to change without notice.

Ruby Compact Bike Geometry

| Size | 440.0 | 480.0 | 510.0 | 540.0 | 570.0 |
|-------------------------------------|---------|---------|---------|---------|---------|
| B-B Drop | 73mm | 73mm | 73mm | 73mm | 71.5mm |
| Chain-Stay Length | 412mm | 415mm | 415mm | 415mm | 417mm |
| Crank Length | 167.5mm | 167.5mm | 170mm | 170mm | 172.5mm |
| Fork Rake | 51mm | 51mm | 51mm | 49mm | 49mm |
| Front-Center | 577mm | 584mm | 587mm | 591mm | 614mm |
| Handle-Bar Width | 360mm | 380mm | 400mm | 400mm | 420mm |
| Head-Tube Angle | 70.25° | 71.25° | 71.5° | 72° | 72° |
| Head-Tube Length | 120mm | 130mm | 145mm | 165mm | 190mm |
| Reach | 358mm | 370mm | 370mm | 374mm | 390mm |
| Seat-Post Length | 350mm | 350mm | 350mm | 350mm | 350mm |
| Seat-Tube Angle | 74.5° | 74.5° | 74° | 74° | 73.5° |
| Seat-Tube Length, B-B Center to Top | 363mm | 391.5mm | 421.5mm | 456.5mm | 486.5mm |
| Stack | 518mm | 531mm | 546mm | 568mm | 590mm |
| Stand-Over Height | 702mm | 721mm | 740mm | 768mm | 792mm |
| Stem Length | 75mm | 75mm | 90mm | 100mm | 100mm |
| Top-Tube Length, Horizontal | 509mm | 522mm | 529mm | 539mm | 566mm |
| Trail | 68mm | 62mm | 60mm | 59mm | 59mm |
| Wheelbase | 977mm | 988mm | 991mm | 995mm | 1021mm |

[Technical Specs...](#)

